

AEREA SUD di MICHELE BRUCOLI



VIALE TOMMASO COLUMBO, 17 - 70123 BARI
TEL. 080.5342454 - 080.5346061
FAX 080.5342441
CELL. 3920619352
SITO INTERNET: WWW.AEREA SUD.IT E.MAIL: tina@brucoli.it



SEL 23



PARTITA IVA 04249100720 - CODICE FISCALE BRC MHL 55B07 A662T - C.C.I.A.A. 302819 - ALBO AGENTI 6701

Noleggino Piattaforme Aeree





VIALE TOMMASO COLUMBO, 17 - 70123 BARI
 TEL. 080.5342454 - 080.5346061
 FAX 080.5342441
 CELL. 3920619352

SITO INTERNET: WWW.AEREA SUD.IT E.MAIL: tina@brucoli.it



SEL 23

23 AJX



Air and water in the cage

Machines in this range are fitted as standard with air/water lines to the cage for use during cleaning or sandblasting and the facades cleaning.

These are standard parts on all our machines.



Emergency pump

A hand operated hydraulic pump ensures emergency movements can be made to recover the machine in case of engine or power failure.



Gear-motor

The rotation movement is carried out through a gear-motor with proportional hydraulic drive that allows soft movements and any efforts to the platform structure.

TECHNICAL FEATURES

TECHNICAL FEATURES

23 AJX

| | |
|----------------------------|--------------|
| Working height | 23,2 |
| Height to the basket floor | 21,2 |
| Max. side outreach | 14,1 |
| Max. capacity in the cage | 200 |
| Jib length | 1,5 |
| Max. length | 7,1 |
| Max. width | 2,4 |
| Stowed machine height | 2,8 |
| Wheelbase | 2,6 |
| Ground clearance | 0,35 |
| Cage dimensions | 1,4 X 0,8 |
| Travel speed km/h | 0-5 |
| External steering radius | 3,2 |
| Turret rotation | 360° |
| Platform rotation | 90°+90° |
| Engine | Hatz 24 kW |
| Controls | Optionals |
| Gradeability % | Proportional |
| Tyres | Optionals |
| Hydraulic tank (lt) | 30/60 |
| Fuel tank (lt) | Filled |
| Total weight | 70 |
| Active oscillating axle | 50 |
| Max. inclination | 12000 |
| Electric circuit | yes |
| Starting battery | 5° |
| Max wind speed Km/h. | 24 V |
| | 2 x 110 AH |
| | 45 |

STANDARD EQUIPMENT

23 AJX

| | |
|-----------------------------|--------|
| Load limiting device | yes |
| Inclinometer | double |
| Emergency descent | yes |
| Travel siren | yes |
| Hour-meter | yes |
| Battery charging indicator | no |
| Lifting and traction hooks | yes |
| Platform colour | yes |
| 2 sets of operation manuals | yes |
| CE Certificate | yes |

OPTIONALS

23 AJX

| | | |
|--------------------------------------|--------------------------------------|------|
| Engine | 3L40 36 Kw HATZ diesel engine | yes |
| Special equipment | 4 WD | yes |
| | 4 WS | yes |
| | Traction battery bio-energy + pump | yes |
| | Automatic battery charger | yes |
| | 2 x 220V 2,7 Kw motor pump | yes |
| | 3 x 380V 5,0 Kw motor pump | yes |
| | 24 V emergency motor pump | yes |
| | Sand anti-penetration kit | n.a. |
| | Oscillating axle | std |
| Platform accessories | Working light | yes |
| | 1000 V insulation working platform | yes |
| | Road lighting | yes |
| | Radio intercom system | yes |
| | Fixed intercom | yes |
| | Anti-collision kit | yes |
| | 220 V power to the basket | yes |
| | Air-water outlet in the cage | yes |
| | Platform 1,6m + load limiting device | yes |
| | Platform 1,8m + load limiting device | yes |
| Platform 2,0m + load limiting device | yes | |
| Tyres | No marking tracks | yes |
| | Tracked chassis | yes |
| Painting | Anti-acid painting | n.a. |
| | Special marine paint | yes |